


## Lampu PJU 120watt Nikkon S433



Street Lantern LED 120watt Nikkon S433

Rating: Not Rated Yet

[Ask a question about this product](#)

Manufacturer [Nikkon LED](#)

### Description

**Lampu PJU 120watt Nikkon S433** adalah jenis lampu penerangan jalan umum LED berkualitas tinggi dengan chip LED LUMILEDS LUXEON Rebel ES (120W) memberikan distribusi cahaya secara maksimal untuk lampu jalan umum. Jenis yang handal dan berdaya guna tinggi, menekan biaya perawatan / pemeliharaan yang secara keseluruhan juga melakukan penghematan pemakaian listrik.

Aplikasi untuk penerangan jalan arteri umum, penerangan jalan bandara, penerangan jalan tol, penerangan jalan kompleks perumahan, penerangan jalan pabrik dan berbagai kebutuhan lainnya.

Parameter teknis **street lantern LED 120watt** ini:

- LED Light Source: \* 3000K LED: LUXEON R
- 3 LED Modules x 14 LUMILEDS LUXEON Rebel ES (90W)
- 4 LED Modules x 14 LUMILEDS LUXEON Rebel ES (120W)
- 5 LED Modules x 14 LUMILEDS LUXEON Rebel ES (150W)
- Typical Luminous Flux & Efficiency @ 700 mA: 280 lm
- Max Junction Temperature: 150°C
- Color Temperature: • 5300K Daylight \*3000K Warmwhite is available upon request

- LED Life Cycle: 50,000 hrs
- Driver: CE, EN55015, EN61000, EN61547
- Luminaire: LM 79, EN 60598-1, EN 60598-2-3, EN62471, EN62493, EN61000-3, EN61547
- Cartoon dimension: 650(L) mm x 340(W) mm x 190(H) mm
- Housing Material: Die-cast aluminium finished with durable polyester epoxy powder coating
  
- Power Supply:
  - - 220 ~ 240 Vac 50 / 60Hz
    - Constant Current : 700mA
    - Dimmable : 1-10V, PWM \* Time Control is available upon request
- Surge Protection: External SPD 10kV, 20kA
- Max System Power Consumption:
  - 95W
  - 128W
  - 158W
- Total Luminous Flux:
  - 9650 lm - 90W
  - 12800 lm - 120W
  - 15400 lm - 150W
- Insulation Classification: Class I
- Ingress Protection: IP66 (Lamp & Gear Compartments)
- Mounting Spigot: ø65mm
- Pole Installation Details (mm): Pole diameter ø42- 60mm
- Nett Weight: 8.2 kg

## Reviews

There are yet no reviews for this product.